
Inlet Port
Top
reference electrode
outlet port
inlet port
reference electrode

FIG._1



FIG._2



FIG._3A



FIG._3B



FIG._3C



FIG._3D



FIG._3E



FIG._3F



FIG._3G



FIG._4A



FIG._4B



FIG._4C



FIG._4D



FIG._4E



FIG._4F


V out
C13
10 uF
R9
1M
1%
C11
0.1 uF
U2
OPA27
C12
0.1 uF
C9
100 uF
C10
100 uF
R10
R7
1k 1%
R6
1k 1%
U1-AA
OPA2277
U1-BA
OPA2277
R6
100k 1%
-12 Reg
RS
100k 1%
R4
1k 1%
C8
0.1 uF
C6
0.1 uF
C7
0.1 uF
R2
R3
Av = (R9/R7)
x (1 + 2R5/R4)
With Values Listed
Av = 20:000
100k C3
10k C4
0.1 uF
0.1 uF
C5
10 uF
Set "0"
With R2
Out
In
Gnd
U3
LM7805
C1
C2
0.1 uF
0.1 uF
Copper
Trace
RTD
R1
0.5
T

FIG._5



FIG._6



FIG._7

FIG._8


Menu Driven
Acquisition
Analysis
ACV
CV
Square
Pulse
Other
Data
Management
Ip, Eo
Analysis
Integration
Other
Temperature
Type Of Scan
Control
On
Control
Off
Single
Repeated
Frequency
Application
Specific
Plotting
Application
Specific
Parallel
Overlay



FIG._9



FIG._10A



FIG._10B

- Bar coded "reference" sheet, stored in tray under unit, with bar coded protocols, bar coded well and slot id's, bar coded commands (e.g. "cancel", "done", etc.)
- Standard bar code wand (preferably with built-in decoder), housed in the tray (hence hidden when not in use)
- Serial (RS-232/485) interface (preferred), or "keyboard wedge"
- Multi-code support (Code 39, Code 128, etc.)
- Bar code on chip carrier (1 code per "8 pack"), identifying test, batch, etc.
    - Peel off labels, with same code as on carrier, with each "8 pack"



FIG._11

- Bar code usage scenario
  - User fills "8-pack" (all 8, or partially) from a 96 well plate, or from individual sample containers (PCR tubes, vaccutainers, etc.)
  - Pull out tray (with bar code reference sheet) and grab wand
  - Scan "start" code
  - Scan protocol code from sheet (will remain in effect until "done" is scanned)
  - Scan chip code from carrier (will remain in effect until "done" is scanned)
  - For each cartridge, user will
    - insert the cartridge in an open slot. Unit senses new chip automatically
    - scan the sample ID by either
      - scanning 96 well plate bar code from plate and well code from sheet
      - or scanning unique sample ID from container
      - or scanning "no ID" from reference sheet
  - Scan "done" code. The protocol can' now be started on these cartridges

FIG._12

- Bar code concept benefits
  - No keyboard entry (all-routine setup can be entered via bar coding)
  - All routine entries accomplished while in front of unit (no going back & forth between PC & Hydra)
  - All bar code entries done from small, flat surface in front of unit
  - No need to label each chip or each slot (which would compromise appearance)
  - Uses small unobtrusive bar code wand, hidden when not in use
  - Is flexible with respect to sample container (tube, 96 well plate, etc.), chip usage (by row of 8, or by individual chip), and lab bar coding method

FIG._13

FIG._14A



FIG._14B



FIG._14C



FIG._14D





FIG._14E



FIG._14F



FIG._15A



FIG._15B



FIG._15C



FIG._15D



FIG._15E



FIG._15F


A Sine Wave And Its Corresponding Vector Notation
θ
Y
X
R
Time
0
Y'
X'
θ'

FIG._16


Polar Coordinates
R
θ
Polar Coordinates'
R
θ'
X
Cartesian Coordinates
Y
X
Cartesian Coordinates'
Y'
X'

FIG._17



FIG._18



FIG._19



FIG._20



FIG._21



FIG._22



FIG._23


2.00E-09
1.00E-09
0.00E+00
-1.00E-09
-2.00E-09
-3.00E-09
-4.00E-09
-5.00E-09
-6.00E-09
-7.00E-09
-8.00E-09
X
(In Amps)
-100
0
100
200
300
400
500
Applied DC Voltage (mV)

FIG._24


1.20E-08
1.00E-08
8.00E-09
6.00E-09
4.00E-09
2.00E-09
0.00E+00
-2.00E-09
-4.00E-09
Y
(In Amps)
-100
0
100
200
300
400
500
Applied DC Voltage (mV)

FIG._25


160
120
80
40
0
-40
-80
-120
-160
X
Y
(Current in nA)
-160
-120
-80
-40
0
40
80
120
160

FIG._26



FIG._27



FIG._28



FIG._29



FIG._30



FIG._31



FIG._32

FIG._33



FIG._34



FIG._35




200
150
100
50
0
-200
-150
-100
-50
0
50
100
150
200
-50
-100
-150
-200

FIG._36


200
150
100
50
0
-200
-150
-100
-50
0
50
100
150
200
-50
-100
-150
-200

FIG._37


200
150
100
50
0
-50
-100
-150
-200
-200 -150 -100 -50 0 50 100 150 200

FIG._38


200
150
100
50
0
-50
-100
-150
-200
-200 -150 -100 -50 0 50 100 150 200

FIG._39


200
150
100
50
0
-50
-100
-150
-200
-200
-150
-100
-50
0
50
100
150
200

FIG._40


1.20E-08
6.00E-09
0.00E+00
-6.00E-09
-1.20E-08
-1.20E-08
-6.00E-09
0.00E+00
6.00E-09
1.20E-08

FIG._41



FIG._42



FIG._43



FIG._44


4.00E-09
3.00E-09
2.00E-09
1.00E-09
0.00E+00
-1.00E-09
-2.00E-09
-3.00E-09
-4.00E-09
90 Degree - 5th Order Polynomial
-100
0
100
200
300
400
500
Applied DC Voltage (mV)

FIG._45


3.00E-09
2.00E-09
1.00E-09
-1.00E-09
0.00E+00
-3.00E-09
-2.00E-09
1.00E-09
2.00E-09
3.00E-09
-1.00E-09
-2.00E-09
-3.00E-09
0.00E+00

FIG._46


Current
1.80E-7
1.70E-7
1.60E-7
1.50E-7
1.40E-7
1.30E-7
1.20E-7
1.10E-7
1.00E-7
9.00E-8
8.00E-8
7.00E-8
6.00E-8
5.00E-8
4.00E-8
3.00E-8
2.00E-8
1.00E-8
0.00E+8
-100 -75 -50 -25 0 25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500

FIG._47



FIG._48



FIG._49



FIG._50


Y (at θ_{opt}) Minus Polynomial
4.0E-08
2.0E-08
0.0E+00
-2.0E-08
-4.0E-08
-6.0E-08
-8.0E-08
-1.0E-07
Current (A)
-100
0
100
200
300
400
500
DC Voltage (mV)

FIG._51


45
35
25
15
5
-5
-15
-25
-35
-45
-55
-65
-75
-85
-95
-105
Current (nA)
Standard Deviation of Positive Values = 8.7 nA
Standard Deviation of Negative Values = 22 nA
0
1
2
3
4
5
6
7
8
9
10
Frequency per mV

FIG._52


Data
15
10
5
0
-5
-10
-15
-0.1
0.1
0.3
0.5

FIG._53


Shifted Data
15
10
5
0
-5
-10
-15
Shifted Left
Shifted Right
0.1
-0.1
0.3
0.5

FIG._54



FIG._55



FIG._56



FIG._57


6.00E-10
4.00E-10
2.00E-10
5.17E-26
-2.00E-10
-4.00E-10
-6.00E-10
-8.00E-10
-1.00E-9
-100
-50
0
50
100
150
200
250
300
350
400
Raw Y
Initial
Guess Y

FIG._58


2n = 2
2n = 16
0
-15
-10
-5
0
5
-10
-15
a - Expected a

FIG._59


c = 0.75
c = 3
0
-15
-10
-5
0
5
-10
-15
a - Expected a

FIG._60


c = 0.15
c = 2
0
95 110 125 140 155 170 185 200 215 230 245 260 275
Width (In mV)

FIG._61



FIG._62



FIG._63



FIG._64



FIG._65



FIG._66



FIG._67


Plasma treatment sequences
Ip (A)
CA
6.0E-06
5.0E-06
4.0E-06
3.0E-06
2.0E-06
1.0E-06
0.0E+00
Ip (A)
80
70
60
50
40
30
20
10
0
CA
Untreated
O2
CF4
O2 + CF4
O2 + H2

Fig. 68


XPS spectra of contaminants on Au
Au(4p)
O(1s)
Au(4d)
Au(4f)
O2 PC+H2 PC
C(1s)
O2 PC
Unclean
Intensity (arb units)
800
700
600
500
400
300
200
100
0
Binding Energy (eV)

Fig 69